



## 0-564-06 - 97dB Tonal Alarm with Mute Function - 9-32VDC

Durite Tonal Alarm with Mute function. Used for warning external hazards of a potential threat when the vehicle is manoeuvring. The IP68 rated speaker is for mounting externally. The speaker is type approved E Marked EMC REG 10.05.



## Wiring

1. RED: Power Input (12/24V)

Connect to Reversing Light (12/24V).

2. BLACK: Ground

Connect to chassis.

3. GREEN: Mute Wire (+)

Connect to headlights for mute night shift function (12/24V)

## Installation

Select a mounting position on the vehicle, which will allow your alarm to operate properly, even in adverse conditions:

- Mount in a position which allows the unobstructed sound projection to the hazard area.
- Mount the alarm securely through fixing holes provided. Hole centre is 75-85mm.
- The unit must not be fitted facing upwards or downwards.
- Protect from impact, flying objects and dirt.
- Keep away from high temperature area around engine or exhaust

## Operation

When fitting is completed, connect the battery earth cable and test for operation.

Test the unit regularly thereafter for proper function.

Warning alarms are strictly meant as safety aids and are not a substitute for proper care and attention while maneuvering a vehicle.

## TECHNICAL SPECIFICATIONS

Type	Tonal Alarm with Mute Function
Voltage	9-32VDC
Sound Pressure	97(+/-4) dB
Current Draw	0.2A @ 12V/ 0.1A @ 24V
IP Rating	IP68 / IP69K
Material Construction	ABS
Mechanical Vibration	10G
Weight	0.200Kg
Dimensions	Please see below
Operating Temperature	-30°C ~ +80°C
Storage Temperature	-30°C ~ +80°C
Certificate	CE, UKCA, E Mark R10 EMC, RoHS

## TECHNICAL DRAWING

