


## **REAR OF VEHICLE**

WIRING KEY									
COLOUR	COMPONENT	TYPE MAX CURRENT (A)	COMMENT						
RED	ROTATORS	9.20	N/A						
GRN	CTR ILLUMINATION	5.80	N/A						
BLK	GROUND	24.3	RING TERMINAL						

## **SPECIFICATIONS**

- 1. FLASH MODE: MAXIMUM 130 FPM
- 2. VOLTAGE (NOMINAL): 12 VDC
- 3. CURRENT (NOMINAL): 7.5 A
- 4. CONNECTION: 14 OR 16 AWG WIRES IN A CABLE
- 5. MOUNTING: 4-BOLT THROUGH MOUNTING KIT
- 6. BASE MATERIAL: ALUMINUM
- 7. LENS MATERIAL: POLYCARBONATE



## NOTES:

- 1. CABLES AND WIRING NOT SHOWN
- 2. TOP VIEW: TOP LENSES NOT SHOWN FOR CLARITY
- 3. MOUNTING FEET: ADD 30mm TO OVERALL HEIGHT
- 4. THE LENGTH BETWEEN MOUNTING FEET IS ADJUSTABLE
- 5. CABLE LENGTH 3.0M (10 ft)
- 6. CABLE EXIT DRIVER'S SIDE
- 7. DIMENSIONS IN MILLIMETERS[INCHES(FOR REFERENCE)]
  8. USE SUB ASSEMBLY (143-00527-60) FOR MANUFACTURE

THE BRAWING AND THE DESIGN IT DISCLOSES ARE THE PRIVATE PROFERTY OF ECCO. AND IS ISSUED IN CONFIDENCE FOR ENGINEERINGINFORMATION. DWILT THE DRAWING AND JOR DESIGN MANY HOTE BLIEDT, COPPED, BEPRODUCED, OR OTHERWISE DISCLOSED THE OR AS A WHOLE TO OUTSIDERS OF UNSED FOR ANY OTHER PURPOSE WITHOUT THE PRIOR WRITTEN CONSENT OF ECCO. THE DRAWING IS SUBJECT TO RECALL AT ANY TIME, YOUR POSSESSION OF THIS DOCUMENT OF COMMENT CONSTITUTES ACCEPTANCE OF THESE TERMS, © 2012 ECCO.

	DO NOT MANUALLY UPDATE. MODEL REFERENCED:A+		APPROVALS	DATE				European Di +44 (0) 113 23	7 5340		
			DRAWN BY MDG	2013-11-15			лШ	Victoria Industrial Park, Seacroft, Leeds			
			CHECKED MPS	2014-01-08		GRO	Ú₽™	Tel: +44 (0)113 2 Fax: +44 (0)113			
			MECH. ENG.					www.eccogro	up.com		
ı	MILLIMETERS DECIMALS	INCHES DECIMALS	ANGLES ± 0.5°	ELEC. ENG.		L/BAR	,60 SER, 1.52N	1, 4 A H	ALO/CTR ILL, C	OC, 12V	
	X.XXX ± 0.02 ± 1/64		TEST ENG.		CUSTOMER PART NO. PRODUCT SERIES: 60 Series Lig				Liahtbars	5	
ı			SALES.								
					SIZE: A	DWG. NO.	60-0	00527-V	REV.		
			Electronically Controlled Use Latest Copy		SHEET 1 OF 1	Project: 09001		Date Created: 2009-02-1	8 B		