

Q-LUX LED WORK LAMPS

NEW WORK LAMP RANGE WITH ROUND, SQUARE AND LOW-PROFILE OPTIONS MANUFACTURED WITH 1W OSRAM LEDS



INTRODUCING THE NEW Q-LUX LED WORK LAMP RANGE, AVAILABLE WITH ROUND, SQUARE AND LOW-PROFILE MODELS IN VARIOUS SIZES AND POWER OUTPUTS.

Ideal for recovery, highways, agricultural and plant/machinery applications, the new Q-LUX LED work lamps are IP68 ingress protected and manufactured with quality 1W OSRAM LEDs to provide an impressive spread of light for various working environments.



KEY POINTS



APPLICATIONS



MAIN FEATURES

- ✓ Heavy duty aluminium housing and polycarbonate lens
- ✓ Flood style beam pattern
- ✓ Manufactured with 1W OSRAM LEDs
- ✓ -30°C to +50°C extreme temperature reliability
- ✓ 304 grade stainless steel fixings and bracket
- ✓ 300mm cable length
- ✓ Deutsch & AMP plugs available upon request

LAP-QLUX-R16W

- ✓ 16 x 1W OSRAM LEDs
- ✓ 1323 effective Lumen
- ✓ Reverse light approval



LAP-QLUX-S16W

- ✓ 16 x 1W OSRAM LEDs
- ✓ 1252 effective Lumen
- ✓ Reverse light approval



LAP-QLUX-F24W

- ✓ 24 x 1W OSRAM LEDs
- ✓ 2145 effective Lumen
- ✓ Reverse light approval



LAP-QLUX-R36W

- ✓ 36 x 1W OSRAM LEDs
- ✓ 2690 effective Lumen



LAP-QLUX-S36W

- ✓ 36 x 1W OSRAM LEDs
- ✓ 2638 effective Lumen



LAP-QLUX-S64W

- ✓ 64 x 1W OSRAM LEDs
- ✓ 3894 effective Lumen



Part Number	Number of OSRAM LEDs	Shape	Effective Lumen	R148 Reverse Light Approved	Dimensions (inc. Bracket)	Current Consumption @ 12V / 24V
LAP-QLUX-R16W	16 x 1W	Round	1323	✓	75 x 85 x 44mm	4.5A / 2.3A
LAP-QLUX-S16W	16 x 1W	Square	1252	✓	75 x 86 x 42mm	4.5A / 2.3A
LAP-QLUX-F24W	24 x 1W	Low Profile	2145	✓	160 x 59 x 53mm	9.5A / 4.8A
LAP-QLUX-R36W	36 x 1W	Round	2690	-	120 x 120 x 49mm	13.5A / 6.8A
LAP-QLUX-S36W	36 x 1W	Square	2638	-	110 x 124 x 49mm	17.5A / 8.8A
LAP-QLUX-S64W	64 x 1W	Square	3894	-	110 x 121 x 61mm	21.5A / 10.8A