

EQUINOX LIGHTBARS

EQUINOX AMBER LED LIGHTBAR RANGE AVAILABLE IN 4 LENGTHS AT 600MM, 900MM, 1200MM & 1500MM.



INTRODUCING THE NEW ECE R65 CLASS II APPROVED EQUINOX LED LIGHTBAR RANGE AVAILABLE IN 4 DIFFERENT LENGTHS AND WITH 44MM LOW PROFILE DESIGN.

Programmed with 3 x ECE R65 approved (single, double and quad) and CAP168 airport flash patterns. Each EQUINOX LED lightbar is also supplied with adjustable mounting feet to suit many shapes and profiles of vehicles.



LAP-EQNX600



HIGHWAY MAINTENANCE



HEAVY GOODS VEHICLES



RECOVERY VEHICLES

KEY POINTS



APPLICATIONS



MAIN FEATURES

- ✓ Multi-voltage (10-30V)
- ✓ 215mm wide design for optimum light output
- ✓ 27 flash patterns including CAP168 airport flash
- ✓ Single, double and quad flash patterns all ECE R65 approved
- ✓ Tough polycarbonate lens and aluminium base
- ✓ Supplied with 3m power cable
- ✓ -30°C to +50°C extreme temperature reliability



LAP-EQNX600



LAP-EQNX900



LAP-EQNX1200



LAP-EQNX1500



LAP-EQNX-1200

Part Number	Mounted Dimensions	Number of LEDs	Current Consumption @ 12V / 24V	Weight
LAP-EQNX600	600 x 215 x 77mm	164	6.0A / 3.2A	2.5KG
LAP-EQNX900	900 x 215 x 77mm	224	6.8A / 3.6A	4.0KG
LAP-EQNX1200	1200 x 215 x 77mm	284	7.4A / 3.8A	5.5KG
LAP-EQNX1500	1500 x 215 x 77mm	344	8.2A / 4.3A	7.0KG



Full 215mm width design



Secure 4-point fixing with adjustable mounting feet