

VAN MASTER VMGHIL310





APPROVALS


 ECE EMC R10, ECE R65 CLASS 1, E-MARKED, CE, UKCA, IP67 / IP69K, CISPR 25 CLASS 3, SAE J595 CLASS 1.

DIMENSIONS

- LIGHT HEAD: W38MM: X D:23MM
- WITH BRACKET: W: 52.5MM X H:42.1MM
- HOLE SIZE REQUIRED: 31.6MM

SPECIFICATIONS

- MULTI VOLTAGE INPUT 9-30VDC.
- 4 X HIGH POWERED LED'S.
- MOUNT: RECESSED FIT WITH 'L' BRACKET (INCLUDED) OR SURFACE MOUNT OPTIONS.
- 21 FLASH PATTERNS.
- SYNC UP TO 12 LIGHTS IN 2 SEPARATE GROUPS.
- WIRE: RED POSITIVE.
 - BLACK NEGATIVE.
- YELLOW FLASH PATTERN SELECTION & SYNC (APPLY TO BLACK FOR NEXT FLASH PATTERN)
 - WHITE LOW LIGHT INTENSITY MODE.
- UP TO 100,000 HOURS RATED LONG-LIFE LED.
- BUILT-IN SELECTABLE FLASH PATTERNS.
- · RECALL FOR LAST FLASH PATTERN USED AT POWER UP.
- WEATHERPROOF AND VIBRATION RESISTANT, JET WASH APPROVED IP69K.
- · ALUMINIUM BASE FOR EXCELLENT HEAT DISSIPATION.
- REVERSE POLARITY PROTECTION
- UV RESISTANT LENS.
- WARRANTY: 3 YEARS.



THE VAN MASTER HIDE-AWAY SERIES PROVIDES THE FUNCTIONALITY OF A WARNING LIGHT IN A LOW PROFILE DESIGN